

Product Overview:

VCL-MX-5010-R-ES is an integrated IEC-61850 compliant ruggedized router with enhanced security equipment with advanced features that may be installed to secure critical infrastructure such as utilities, sub-stations, smart-grid distribution systems, airports and railways as well as IT Networks of financial institutions such as banks and corporate networks.

VCL-MX-5010-R-ES is password protected with capabilities that meet and exceed NERC as well as all mandatory requirements of password protection and control.

IPSEC VPN
12.2 GBPS

ROUTER WITH E-SEC
24.4 GBPS

NGFW
24.4 GBPS

THREAT PROTECTION
20.2 GBPS

Interfaces:

- 4 x 10/100/1000BaseT RJ-45

- 8 x 10/100/1000BaseT RJ-45 or 1G Optical (SFP) - Configurable

- 2 x 10/100BaseT RJ-45

- 1 x RS-232 (RJ-45)

- 1 x 10/100/1000BaseT RJ45 Secure Management (OAM) Port



Additional features of GUI:

- User controlled GUI
- Logs accessible anytime
- Live Threat and traffic monitoring tools
- View network Usage
- Change Credentials
- Smart quick search.

Captive Portal in VCL-MX-5010-R-ES

Captive Portal allows the customer to force authentication, or redirection to a click through page for network access. This is commonly used in hotspot networks and corporate networks for an additional layer of security on wireless or internet access.

Highlights:

- Ruggedized, IEC-61850-3 compliant firewall
- High-reliability hardware
- Suitable for 1+0 non-redundant and 1+1 redundant installation with automatic failover
- Designed to be installed in sub-stations, SCADA networks and industrial / harsh environments
- Secure Boot
- Firewall Security:
 - Inclusion Policy - Access Control based upon White List IP addresses, MAC address and IP Domain
 - Exclusion Policy - Access Control based on Black-List Continuous monitoring of the TLS connection to nullify MitM attacks.
- Brute Force attack mitigation
- Content filtering
- Non-volatile Access Log with capability to "fingerprint" all successful and failed log-in attempts and keep a log of the IP addresses of all successful and failed logins / login attempts.
- Resistance to Denial of Service (DoS) Attack
- Prevention of DDoS & DoS-added
- SSH (Secure Access Control) with encrypted password protection
- SYN cookie protection
- Zone based IP spoofing
- Malformed packet protection
- DNS guard features
- Antivirus, Anti-worm, anti-spam and anti-spyware protection
- Anti-APT (or Anti BOT), Adv Persistent Threat

VCL-MX-5010-R-ES offers a wide range of VPN technologies ranging from modern SSL VPN's to IPsec. Site-to-Site and road warrior setups are possible and with the integrated OpenVPN client exporter, the client can be configured within minutes.

Routing Features and Capabilities:

- OSPF v2 and V3
- RIP v1, RIP v2
- BGPv4
- ARP, IP Forwarding
- Static routing, VLAN based routing, NATL1, CARP redundancy support tracking
- 802.1Q VLAN
- ACL Layer 2/3 Security
- Layer 2/3 Routing, Dynamic Discovery Routing
- TCP/IP, UDP, DHCP
- SNMPv2/v3
- Remote access authentication via RADIUS
- IEEE 1613
- IEC 61850-3, IEC 60068-2-27, IEC 60068-2-6 compliance
- QoS
- IP Forwarding
- Detailed system logging
- Multiple IP address supported.

Security - Features and Capabilities:

- Next Generation Firewall (NGFW)
 - Allows firewall rule creation for each port, independently.
 - May be installed in non-redundant 1+0 or redundant 1+1 in an automatic failover* configuration. Support active-active mode
 - Deep Packet Inspection (DPI)
 - Point-to-Point and Point-to-Multipoint applications
 - IPv4 & IPv6 support
 - Unified NMS – Up to 1000 devices may be configured and managed through unified NMS.
 - HTTP based smart GUI for individual nodes
 - Per-frame/packet authentication
 - Support NAT, PAT & Policy based NAT/PAT, Mapped IP (MIP), Virtual IP(VIP), VoIP protocols
 - Authentication protocols: RADIUS, LDAP support
 - Supports IKE, IKEv2, PKI (X.509)
 - Maximum Concurrent Sessions: 8,300,000
 - New Connections per second: 150,000
 - 802.1Q VLANs : 4,094
 - Filtering of protocols like FTP, SMTP, HTTP, HTTPS, SNMP, UDP, ICMP, RPC, DNS, DHCP, ARP, TCP, POP3
 - Security:
 - Port based, MAC based, IP Address based
 - IP Domain based
 - Protocol type
 - URL based
 - Whitelist and blacklist options:
 - Allows traffic based on user configured rules
 - Two-factor Authentication with time-based OTP for secure access
 - Traffic Shaper
 - Forward Caching Proxy (transparent) with Blacklist support
 - Virtual Private Network (OpenVPN site to site and remote VPN client support)
 - Supports upto 500 IPsec Site to Site Tunnels
 - High availability and hardware ethernet failover*
 - Intrusion Detection and Prevention
 - Built-in reporting and monitoring tools including real-time graphs
 - Network Flow Monitoring
 - DNS Server, DNS Forwarder, Dynamic DNS
 - DHCP Server and Relay
 - Stateful inspection firewall
 - Granular control over state table
 - MAC layer filtering
 - VXLAN supported
 - Infrastructure neutral
 - Transparent to network and applications
 - Easy installation and management
 - LDAP user authentication support
 - Export logs locally or on a server.
- *Redundant device Failover switching with VCL-Ethernet Failover Switch.

Encryption Algorithms:

- AES-128, AES-192, AES-256
- 128 bit AES-GCM with 128 bit ICV
- 192 bit AES-GCM with 192 bit ICV
- 256 bit AES-GCM with 256 bit ICV
- Camellia 128, 192, 256
- Blowfish 128, 192, 256
- 3 DES, CAST 128, DES

Hash Algorithms:

- MD5, AES-XCBC
- SHA 1, SHA 256, SHA 384, SHA 512

Typical VCL-MX-5010-R-ES Deployments:

- Utilities - Power, Oil and Gas Installations.
- Industrial Applications.
- Campus IP Networks, for all types of data, voice and video over IP applications
- MPLS meshed-networks
- Metro Ethernet and VPLS networks
- Cloud applications

Physical Dimension:

- 19 inch, 1.5U High Rack Mount
- D x W x H: 260mm x 477mm x 67mm
- Net Weight: 5.0 Kgs
- Gross Weight: 10.7 Kgs

Technical Specifications:

Integrated Storage Drive	Internal, soldered 16GB High Performance SATA Drive
Additional Storage	M.2 SATA - 120GB, 240GB, 500GB and 1TB SSD Options
Power Supply	Dual (1+1) Redundant Power Inputs * (Power Supply Options)
Indicators and Alarms	2 x Power Supply LED indicator
Processor	Quad Core up to 2.4 GHz per core
RAM (DDR 3L)	4GB
Performance	Ruggedized Industrial
MTBF (hours)	101292
IP Level Protection	IP20
Power Consumption @ 48V DC	30 Watts
Power Consumption @ 80~240, 50/60Hz VAC	35 Watts

Environmental:

Operating Temperature	-4°F ~ 149°F (-20°C ~ 65°C)
Storage Temperature	-40°F ~ 185°F (-40°C ~ 85°C)
Operating Humidity	10%~95% relative humidity, non-condensing
Storage Humidity	10%~95% @40°C; non-condensing

EMI, EMC, Surge Withstand and other Compliances:

EN 50081-2	EN 50082-2	IEC 60068-2-29
IEC 61000-4-6 (Conducted Immunity)	IEC 60068-2-6	IEC 60068-2-2
IEC 60068-2-78	IEC 60068-2-1	IEC 60068-2-14
CISPR 32 / EN55032 Class A (Conducted Emission and Radiated Emission)		
IS 9000 (Part II Sec. 1-4, Part III Sec. 1-5, Part IV, Part 14 Sec. 1-3)		
IEC 60870-2-1	IEC 61000-4-5	
IEC 61000-4-3 (Radiated Immunity)	IEC 61000-4-8	
IEC 61000-4-2	IEC 61000-4-11	IEC 61000-4-4
Telcordia GR-1089 Surge and Power Contact		

CE Compliance:

- Low Voltage Directive 2014/35/EU (48V DC Version)
- Electromagnetic Compatibility 2014/30/EU

Other Regulatory Compliances:

- RoHS,
- CE Marking
- Complies with FCC Part 68 and EMC FCC Part 15
- Telcordia GR-1089 Surge and Power Contact

Ordering Information:

Part#	Description
VCL-MX-5010 -R-ES	VCL-MX-5010-R-ES, Router 19 Inch 1.5U High Rack Mount - Graphical User Interface (GUI) - Installation Kit: System Core Cables Add *Power supply options

*** Power Supply Options:**

AC088~265R	2 x 88~265V AC Power Supply Inputs [1+1 Redundant Power Supply]
DC090~260R	2 x 90~260V DC Power Supply Inputs [1+1 Redundant Power Supply]

© Copyright : Valiant Communications
 Technical specifications are subject to changes without notice.
 Revision – 1.3, January 10, 2023

U.S.A.
 Valcomm Technologies Inc.
 4000 Ponce de Leon Blvd.,
 Suite 470, Coral Gables,
 FL 33146, U.S.A.
E-mail: us@valiantcom.com

U.K.
 Valiant Communications (UK) Ltd
 Central House Rear Office,
 124 High Street, Hampton Hill,
 Middlesex TW12 1NS, U.K
E-mail: gb@valiantcom.com

INDIA
 Valiant Communications Limited
 71/1, Shivaji Marg,
 New Delhi - 110015,
 India
E-mail: mail@valiantcom.com